

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4970)

Set cor. to secs. 2, 3, 10, & 11, from which

- A fir, 10" dia., bears N.85°E., 19 lks.
- A fir, 18" dia., bears S.65°E., 19 lks.
- A fir, 12" dia., bears S.75°W., 17 lks.
- A fir, 8" dia., bears N.35°W., 17 lks.

Douglas Co. Surveyors Office - Ben B. Irving, County Surveyor - Witnesses: H.C. Carey & R.C. Kerchner - March 22, 1945 - C.S. File 38/46

Identified from 3 OBTs - Remarkd OBTs
 Marked a fir 24" N.10°E., 24.6 ft.
 Set stone 12x15x24" marked 5 notches S. 2 notches E. I Notch N. 4 notches W.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12424-5)

The cor. of secs. 2, 3, 10, & 11, perpetuated & recorded by Irving, in 1945, at record bearing and distance from the original BTs, monumented with a stone, 24x15x12", firmly set, with 5 notches on the S, 2 notches on the E, 1 notch on the N, & 4 notches on the W edge, from which the original BTs:

- A rotted fir stump, 12" dia., bears N.85°E., 19 lks.
- A fir, 30" dia., bears S.65°E., 19 lks., bark scribed T27S R3W S11 CS BT, by the county surveyor.
- A fir, 22" dia., bears S.75°W., 17 lks., bark scribed T27S R3W S10 CS BT, by the county surveyor.
- A fir, 15" dia., bears N.35°W., 17 lks., bark scribed T27S R3W R3 CS BT, by the county surveyor.

and county surveyors bearing tree:
 A down fir, 24" dia., bears N.10°E., 37 lks.

At the corner point
 Set an iron post, 28 ins, long, 2½" dia., 26" in the ground, with brass cap mkd.

T27S	R3W
S 3	S 2
S 10	S 11

1958

from which

- A fir, 12" dia. bears N.59°E., 39 lks. mkd: T27S R3W S2 BT
- A fir, 17" dia bears S.31½°E. 53 lks. mkd: T27S R3W S11 BT
- A W.Oak, 7" dia bears S.37°W. 125 lks mkd: T27S R3W S10 BT
- A fir, 33" dia. bears N.12½°W. 55 lks. mkd: T27S R3W S3 BT

Deposit County Surveyor's corner stone alongside iron post

cont.TOW

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Lance J. Bishop & Wayne L. Rogers, Cadastral Surveyors, under Group #1189, surveyed May/July 1984 - (DCSO records Vol. 47 Page(s) 17957)

The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A fir stump, 30" dia., bears S.65°E., 19 lks., with faint scribe marks visible on bark.
- A fir stump, 27" dia., bears S.75°W., 17 lks., with scribe marks T27S R3W visible on bark blaze.
- A fir, 17" dia., bears N.35°W., 17 lks., with scribe marks T27S R3W S3 visible on bark blaze.

and a BT mkd. by Ben B. Irving, County Surveyor, in 1945

- A root hole, with down fir alongside, 24" dia., bears N.10°E., 37 lks., no marks visible.

and bearing trees mkd. by Corbin

- A fir, 19" dia., bears N.59°E., 39 lks., with healed blaze
- A fir, 20" dia., bears S.31½°E., 53 lks. with healed blaze
- A W.Oak, 9" dia. bears S.37°W., 125 lks. with healed blaze
- A fir, 35" dia., bears N.12½°W., 55 lks. with healed blaze

Fd. Ok by M. Heimburger, 3/1994 - M118-54
Fd. Ok by M. Heimburger, 10/1997 - M122-68

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2258, Surveyed April/June 2009 - (DCSO records Vol. 57 Page(s) 22674-5)

The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A roothole bears S.65°E., 12.5 ft., alongside of which is an uprooted, sawed fir stump, 32" dia., with no marks visible.
- A decayed fir stump, size indeterminate, bears S.75°W., 11.2 ft., with no marks visible.
- A fir, 23" dia., bears N.35°W., 11.2 ft., with scribe marks R3W CS BT visible on the bark.

and the remains of a bearing tree mkd. by Irving, in 1945

- A roothole bears N.10°E., 24.4 ft., alongside of which is an uprooted, decayed fir snag, size indeterminate, with no marks visible.

and the remains of bearing trees mkd. by Corbin

- A fir, 26" dia., bears N.59°E., 25.7 ft. with a healed blaze.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 21" dia., bears S.31½°E., 33.0 ft., with a healed blaze. (Record, 35.0 ft.)
A decayed oak snag, 9" dia., bears S.37°W., 82.5 ft., with no marks visible.
A fir, 39" dia., bears N.12½°W., 36.3 ft., with a healed blaze.
and a new bearing tree
A fir, 8" dia., bears S.42¼°W., 42.0 ft., mkd. T27S R3W S10 BT.
Corner is located on a S. slope

Bartt Heichel - For: Linnea Torkeisen - 8/2023 - M182-60

Found - 2½" dia. iron post, projecting 6" above ground, with brass cap properly marked (1958 BLM) From which:
24" Fir (rec 23") bears N.35°W., 11.2' with "R3W CS BT" scribe marks visible on the bark.
27" Fir (rec 26") with healed blaze, bears N.59°E., 25.7'
22" Fir (rec 21") with healed blaze bears S.31°30'E. 33.0'
39" Fir, with healed blaze bears N.12°30'W., 36.3'
10" Fir (rec 8") with healed blaze bears S.42°15'W., 42.0'