



TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

FD. Ok by Ronald Geisler, 2/1987 M103-61  
Fd. Ok by Bruce Shaner, 2/1995 M121-49

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2258, Surveyed April/June 2009 - (DCSO records Vol. 57 Page(s) 22678-9)

-----  
The 1/4 sec. cor. of secs. 2 & 3, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground (alongside of which is an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remaining original bearing tree

A fir, 33" dia., bears N.80°E., 46.9 ft., with a healed blaze.

and the remains of bearing trees mkd. by Byron, in 1954

A yew, 10" dia., bears S.49°E., 30.4 ft., with a healed double blaze.

A fir stump, 10" dia., bears S.76½°W., 107.9 ft., with fragmentary scribe marks visible on a partially healed blaze.

and bearing trees mkd. by Corbin

A cedar, 20" dia., bears N.74½°E., 62.0 ft., with a healed blaze.

A fir, 44" dia., bears S.39°W., 65.3 ft., with a healed blaze.

Corner is located on a S. slope