

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35 of T.26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4352)

Set post, cor. to secs. 34, 35, 2 and 3, around which a mound
of stones was raised, as per instructions.

James W. Byron, Ray Irving - DCSO - April 1954 - C.S. File
46/20

Found 1¼ inch shaft and mound of stone.

BLM survey by Harold D. Corbin, Group No. 350, Survey Aug/Nov.
1958 (DCSO records, Volume 29 Page 12412)

Found corner monumented with an iron pipe, 1" dia., firmly
set, 6" above ground, in a very old mound of stone, 2½ ft.
base, 1 ft. high. Accept this mound of stone as the best
available evidence of the original corner.
At the corner point, set an iron post, 28" long, 2½" dia., 22
ins. in the ground, rebuild the old mound of stone around the
iron post, 2½ ft. base, to top, with brass cap mkd.

T 26 S R 3 W
S 34 | S 35
S 3 | S 2
T 27 S
1958

from which

A Fir 26" dia., bears N.39¾°E., 571 lks., mkd. T26S R3W
S35 BT.

A twin Cedar 18" dia., bears S.32½°E., 425 lks. mkd. T27S
R3W S2 BT.

A White Oak 14" dia., bears S.51½°W., 675 lks. mkd. T27S
R3W S3 BT.

A White Oak 20" dia., bears N.66°W., 295 lks. mkd. T26S
R3W S34 BT.

Deposit iron pipe alongside iron post.

Found BC and 4 BTs, BLM, Wayne Rogers Group #1058, June/Aug.
1981 - (DCSO records, Volume 45 Page 17433)

Found OK by D. Edwards, May 2004 - M144-48

Fd. Ok by D. Edwards, Oct. 2006 - M151-58