

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882  
- (DCSO records Vol. 12 Page(s) 4978)

-----  
Set Laurel post 3 ft. long, 4" sq., for ¼ sec. cor. mkd. S C  
¼ S on N. face, from which

A Fir 18" dia., bears N.65°W., 65 lks. dist. mkd. S C ¼ S  
BT.

A Fir 72" dia., bears S.85°E., 110 lks. dist. mkd. S C ¼  
S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John  
Powell & Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-47

-----  
Found - Orig. 18" Fir N.65°W., 42.9 ft., shows good bark  
scribing.

Orig. 72" now 90" Fir S.85°E., 67.0 ft., not 72.6  
ft., dead.

Found 3/4" I.Rod at corner and rock mound.

A 3/4" I.R. bears East, 13.6 ft. May have been set  
for North ¼ S. 2

Rescribe now 40" R.Fir N.65°W., 45.9 ft. "¼ S35 CS BT"

New BT - 9" Laurel bears S.85°E., 21.4 ft. "¼ S CS BT".

BLM Resurvey by Boyd W. Peterson and Mark D. Dixon, Cadastral  
Surveyors, under Group #1268, surveyed May/Sept. 1985 - (DCSO  
records Vol. 48 Page(s) 18203-04)

-----  
The standard ¼ sec. cor., perpetuated and recorded by Byron  
in 1862, monumented with an iron rod 3/4" dia., firmly set,  
projecting 18" above a mound of stone, 3 ft. base, 1½ ft.  
high, from which the remains of original bearing trees:

A Fir snag 80" dia., bears S.85°E., 97 lks. dist., burned  
with no marks visible. (Rec. 110 lks.)

A double Fir 72" dia., bears N.65°W., 68½ lks. dist., with  
fragmentary scribe marks visible on bark blaze and a  
healed blaze. (Rec. 65 lks.)

and a bearing tree mkd. by Byron:

A Madrone 10" dia., bears S.84°E., 32 lks. dist., with  
healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 6" in the  
ground, to solid rock, directly over iron rod, in a mound of  
stone, 4 ft. base to top, with brass cap mkd. SC

T 27 S R 3 W

¼ S 35

1985

(Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree:

A Fir 7" dia., bears N.59¼°E., 68 lks. dist., mkd. ¼ S325  
SC BT.

Deposit white "DEEP-1" magnetic marker at base of stainless  
steel post.

From this point, a point established by person(s) unknown,  
bears N.89°53'E., 0.20 chs. dist. monumented with an iron  
rod, 3/4" dia., firmly set, projecting 12" above ground.