

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Boyd W. Peterson & Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May/Sept. 1985 - (DCSO records Vol. 48 Page(s) 18222)

Point for the center ¼ sec. cor. of sec. 25, at intersection with the E & W center line.

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:

T27S R3W
C¼ S35
1985

from which

A fir, 7" dia., bears S.88°E., 28 lks., mkd: C¼ S35 BT.

A fir, 5" dia., bears S.70°W., 12 lks., mkd: X BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 2/17/2019 - Filed 7/2025 - C.S. File 67/60-48

Found - BLM 3½" Brass cap proj 3"
21" Fir S.88°E. 18.0 ft (Rec 28 lks)
18" D.Fir S.70°W. 7.9 ft (Rec 12 lks) fully healed low blaze.

New - 17" D.Fir N.50°E. 20.7 ft scribed C ¼ S35 CS BT
18" D.Fir N.26½°W. 17.4 ft scribed C ¼ S35 CS BT

Notes - Corner is approx 150ft west of access road.

Compass decl. 14¾°E.