

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Ben B Irving, Co. Surveyor - Milo Godfrey - Lester Kershner - May 14, 1947 - C.S. File 38/187 & M16-77

-----

I set a 1"x36" iron pipe with a brass cap stamped "County Surveyor Office C<sup>1</sup>/<sub>4</sub>S 23" for the center <sup>1</sup>/<sub>4</sub> section corner & from which a fir 12" in dia., bears S.30°W., 44.4 ft. & a fir 10" dia., bears N.3°E., 45.9 ft.

Fd. 6/1979 BLM  
Fd. 1/1981 M87-9

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - 7/28/1981 - C.S. File 61/27-25

-----

Found - Brass cap per 1947 renewal firmly set, protruding 12" out of ground & (properly) marked.  
12" now 13" fir, down, with well-healed double blaze bears S.28°W., 45.4 ft. (rec. S.30°W., 44.4) to stump hole (1947)  
10" now 20" fir stump, cut low with possible partial blaze bears N.6°E. 46.1 ft (Rec N.3°E. 45.9) 1947  
New BTs- 10" fir bears N.14°W., 34.5 scribed C<sup>1</sup>/<sub>4</sub> S23 CS BT in double blaze.  
12" fir bears N.41°E., 41.4 scribed C<sup>1</sup>/<sub>4</sub> S23 CS BT in double blaze.  
10" fir bears S.3°E., 12.0 scribed C<sup>1</sup>/<sub>4</sub> S23 CS BT in double blaze.  
14" Fir bears S.32<sup>1</sup>/<sub>2</sub>°W., 50.7 scribed C<sup>1</sup>/<sub>4</sub> S23 CS BT in double blaze.  
DCSO BT tags on all trees.

FD. by D. Bentz March 1984, M96-28

BLM Dependent resurvey by Boyd W. Peterson & Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May/Sept. 1985 - (DCSO records Vol. 48 Page(s) 18217-8)

-----

The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 23, established & recorded by Irving, in 1947, perpetuated and recorded by Quibell, in 1981, and is accepted as the corner, monumented with an iron post, 1<sup>1</sup>/<sub>2</sub>" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd.  
from which the remains of bearing trees mkd. by Irving  
A sawed fir stump, 20" dia., bears N.6<sup>1</sup>/<sub>4</sub>°E., 70 lks., no marks visible.  
A root hole bears S.29°W. 69 lks. with down fir alongside, 13" dia., with healed double blaze. cont....

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 540340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Quibell  
A fir, 13" dia., bears N.41 $\frac{3}{4}$ °E., 63 lks., with scribe marks C  $\frac{1}{4}$  S23 CS BT visible on partially healed blaze.  
A W.Fir, 11" dia., bears S.3°E., 18 lks., with scribe marks C  $\frac{1}{4}$  S23 CS BT visible on partially healed blaze.  
A W.Fir, 15" dia., bears S.32 $\frac{1}{2}$ °W., 77 lks., with scribe marks C  $\frac{1}{4}$  S23 CS BT visible on partially healed blaze.  
A fir, 11" dia., bears N.14°W., 52 lks., with scribe marks 3 CS BT visible on partially healed blaze.

FD. by D. Bentz 7/1990 M110-37  
Fd. by D. Bentz 11/1993 M118-16  
Fd. 8/1995 K. DeGroot, 1995-0102A&B