

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 35 & 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4978)

Set Maple post 4 ft. long, 4" sq., firmly in the ground, for standard cor. to secs. 35 and 36, mkd. S C T27S R3W on N.; Sec. 36 on E.; and 35 on W. faces, with 1 notch on E. and 5 notches on W. faces, from which

- A Laurel 14" dia., bears N.55°E., 48 lks. dist. mkd. SC T27S R3W S36 BT.
- A Laurel 20" dia., bears N.42°W., 77 lks. dist. mkd. SC T27S R3W S35 BT.
- A Fir 36" dia., bears S.35°W., 63 lks. dist. mkd. T28S R3W S2 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-46

Found - Orig. 14" now 17" Laurel, shows good scribing. No other orig. BTs found. Find 3/4" Iron rod at corner and a 3/4" I.R., 9.2 ft. East (14 lks.) which is record for CC Secs. 1 & 2

New BTs- 8" R.Fir bears N.82°E., 19.7 ft. scribed S36 CSBT. 15" R.Fir bears N.79°W., 55.0ft. scribed S35 T28S R3W CS BT.

We find 48" R.Fir bears N.61°E., 52.7 ft., shows good bark scribing. This BT may have been scribed for CC 1 & 2, T28S, but not of record.

BLM Resurvey by Boyd W. Peterson and Mark D. Dixon, Cadastral Surveyors under Group #1268, surveyed May/Sept. 1985 - (DCSO records Vol. 48 Page(s) 18203)

The standard sec. cor. perpetuated and recorded by Byron in 1962, from original evidence which is no longer in existence, monumented with an iron rod 3/4" dia., loosely set and bent over, protruding 10" above ground, from which a bearing tree mkd. by Byron:

- A Fir 16" dia., bears N.79°W., 82 lks. dist., with healed blaze.

At the corner point
Set a stainless steel post 28" long, 2½" dia., 22" in the ground with brass cap mkd.

SC
T 27 S R 3 W
S 35 | S 36

1985

(Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree
A Maple 11" dia., bears N.37½°E., 97 lks. dist. mkd. T27S
R3W S36 SC BT.
Deposit iron rod alongside stainless steel post.

From this point, a point established by person(s) unknown,
bears East 0.14 chs.dist. monumented with an iron rod, 3/4"
dia., firmly set, projecting 4" above ground.