

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4986)

Set Maple post, 3 ft. long, 4" sq., firmly in the ground, for 1/4 sec. cor., marked 1/4 S on E & W face; from which
A fir, 12" dia., bears S.25°W., 22 lks., mkd: 1/4 S BT.
A maple, 8" dia., bears N.30°E., 12 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Boyd W. Peterson & Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May/Sept. 1985 - (DCSO records Vol. 48 Page(s) 18206)

The 1/4 secs. cor. of secs. 35 & 36, determined from the remains of the orig. BTs

A maple stump, 16" dia., bears N.53 3/4°E., 12 lks., lks., with a rotted blaze & old axe marks in overgrowth (Rec. N.30°E.)

A fir, 20" dia., bears S.31°E., 22 lks., with scribe marks BT visible on opened blaze. (Rec. S.25°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 14" in the ground, to solid rock, in mound of stone, 3 ft. base, to top, with brass cap marked:

T27S R3W
1/4
S 35|S 36
1985

from which new BTs

A fir, 19" dia., bears S.64 3/4°E., 77 lks., mkd: 1/4 S36 BT.

A fir, 14" dia., bears N.16 1/4°W., 34 1/2 lks., mkd: 1/4 S35 BT.