

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4986)

-----  
Set cedar post, 4 ft. long, 4" sq., for cor. to secs. 25, 26, 35, & 36, firmly in the ground, and marked T27S R 3 W S 25 on NE, S 26 on NW, S 35 on SW, S 36 on SE faces, with 1 notch on E & S edges; from which  
A laurel, 16" dia., bears N.65°E., 47 lks., mkd: T27S R3W S25 BT.  
A B.Oak, 12" dia., bears N.30°W., 104 lks., mkd: T27S R3W S26 BT.  
A Laurel, 12" dia., bears S.60°W., 87 lks., mkd: T27S R3W S35 BT.  
A Laurel, 14" dia., bears S.53°E., 66 lks., mkd: T27S R3W S36 BT.

Douglas Co. Surveyors Office - John Powell - W. Penley & J. Heritage - July 1970 - C.S. File 54/40-189

-----  
Found - 16" Laurel, now 18" burnt out, N.80°E., (rec. N.65°E., 31.0 ft. has very good face, burnt off.  
14" Laurel, now 17" S.53°E., 43.6 ft opened for faint but definite scribe marks on rotted face.  
No trace of SW or NW BTs  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R3W  
OFFICE S 26|S 25  
1970 S 35|S 36  
New BTs- 39" D.Fir S.74°E., 65.0 ft. mkd: T27S R3W S36 CS BT.  
6" D.Fir S.58°W., 7.9 ft. mkd: T27S R3W S35 CS BT.  
6" Laurel N.49°W., 4.3 ft. mkd: T27S R3W S26 CS BT.  
8" Laurel N.33°E., 10.7 ft. mkd: T27S R3W S25 CS BT.

Ronald G. Geisler, LS 1988 - For: Champion International Cor. - Jan. 1984 - M95-77 & C.S. 58/278

-----  
Found - 1970 Douglas County brass cap on iron pipe.  
9" laurel bears N.33°E. 10.4 ft (Rec 10.7 ft) scribed T27S R3W S25 CS BT.  
7" laurel bears N.49°W., 4.3 ft scribed T27S R3W S26 CS BT.  
8" fir bears S.58°W. 8.2 ft (Rec. 7.9 ft) Closed face  
43" fir stump bears S.74°E., 64.7 ft. (Rec. 65.0 ft.) Scribe marks visible.  
22" laurel, portion of the base burnt out, bears N.80°E., 29.8 ft. (Rec. N.65°E., 31.0 ft) No scribing. (Original)  
20" laurel stump bears S.53°E., 42.7 ft. (Rec. 43.6 ft.) No scribing. (original). cont next pg

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>New BT - 7" canyon live oak bears S.71°E., 24.5 ft. scribed: T27S R3W S36 BT.</p>
<p>Fd. &amp; used on BLM Dependent resurvey by Boyd W. Peterson &amp; Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May/Sept. 1985 - (DCSO records Vol. 48 Page 18211)</p>
<p>Fd. Ok D. Edwards, 2/2002 - C.S. File 65/41-4</p>
<p>BLM dependent resurvey by A. Bert Skeesick &amp; Timothy J Moore, Cadastral Surveyors &amp; Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22040-1)</p> <p>-----</p> <p>The cor. of secs. 25, 26, 35, and 36, remonumented by the Douglas County Surveyors Office, in 1970, monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees</p> <ul style="list-style-type: none"><li>A laurel, 22" dia., bears N.80°E., 29.7 ft., no marks visible. (Record, N.65°E., 31.0 ft.)</li><li>A laurel stump, 25" dia., bears S.55¾°E., 42.9 ft., no marks visible. (Record, S.53°E., 43.6 ft.)</li></ul> <p>and the remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <ul style="list-style-type: none"><li>A laurel, 10" dia., bears N.28½°E., 10.6 ft., with a healed double blaze.</li><li>A sawed fir stump, 44" dia., bears S.76°E., 64.7 ft., with scribe marks T27S R3W S36 CS BT visible on a partially healed double blaze.</li><li>A fir, 14" dia., bears S.58°W., 8.3 ft., with a healed double blaze.</li><li>A laurel, 7" dia., bears N.49°W., 4.6 ft., with scribe marks T27S R3W S26 CS BT visible on a partially healed double blaze.</li></ul> <p>and a bearing tree mkd. by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1984</p> <ul style="list-style-type: none"><li>An oak, 8" dia., bears S.71°E., 24.4 ft., with scribe marks 27S W 5 BT visible on a partially healed blaze.</li></ul>
<p style="text-align: right;">2</p>