

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4987-8)</p> <p>-----</p> <p>Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd on E & W faces, 1/4 S, from which</p> <p> A cedar, 30" dia., bears S.85°W., 43 lks., mkd: 1/4 S BT.</p> <p> A fir, 18" dia., bears N.35°E., 80 lks., mkd: 1/4 S BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood - Jan. 1969 - C.S. File 51/254-26</p> <p>-----</p> <p>Found - 18" D.Fir now 42" N.39°E. 52.8 ft. faint bark scribe 30" Cedar, S.80°W., 28.4 ft. down & burned.</p> <p>Set - 2 1/2" Alum. cap: Section 26, Section 25 1969</p> <p>New BTs- 12" Cedar S.60 1/2°E., 30.0 ft. mkd: 1/4 S25 BT. 9" D.Fir S.20°W., 3.8 ft. mkd: 1/4 S26 BT.</p>
<p>Fd. Ok by D. Edwards 2/2002 - C.S. File 65/41-4</p>
<p>BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22041-2)</p> <p>-----</p> <p>The 1/4 sec. cor. of secs. 25 and 26, remonumented by Shrum, in 1969, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with aluminum cap (properly) mkd from which the remains of the original bearing trees</p> <p> A fir snag, 40" dia., bears N.35°E., 52.8 ft., no marks visible.</p> <p> A roothole, bears S.74 1/4°W., 27.6 ft., with decayed and burnt cedar trunk, size indeterminate, lying alongside, no marks visible. (Record S.85°W., 28.4 ft.)</p> <p>and the remains of bearing trees mkd. by Shrum</p> <p> A sawed cedar stump, 13" dia., bears S.60 3/4°E., 29.7 ft., with fragmentary scribe marks 1/4 S25 visible on a partially healed blaze.</p> <p> A fir, 15" dia., bears S.22 3/4°W., 4.5 ft., with a healed double blaze.</p> <p>and a new bearing tree</p> <p> A cedar, 10" dia., bears S.57 1/2°E., 37.4 ft., mkd. 1/4 S25 BT</p>
<p>Ron Rice - For: Seneca Jones Timber Co. - May 2013 - M165-24</p> <p>-----</p> <p>Found - 2 1/2" USPC alum. Cap dated 1969 with the following accessories:</p> <p> 40" D.Fir snag bears N.35°E., 52.8', no marks</p> <p>continued next page</p>

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" cedar stump bears S.60 $\frac{3}{4}$ °E., 29.7', scribing visible
17" D.Fir bears S.22 $\frac{3}{4}$ °W., 4.5', healed face
13" I.Cedar bears S.57 $\frac{1}{2}$ °E., 37.4', healed face
Steel post adjacent to corner