

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4989)

Set dogwood post, 3 ft. long, 4" sq., firmly in the ground for ¼ sec. cor. mkd on E & W faces, ¼ S, from which
A fir, 18" dia., bears N.43°E., 28 lks., mkd: ¼ S BT.
A cedar, 14" dia., bears N.78°W., 25 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Ben B. Irving, DSC - Wit: Milo Godfrey & Lester S. Kershner - May 14, 1947 - C.S. 38/187

Reblazed & rescribed orig. BTs
Fir 18" dia., (now 36") N.48°E., 28 lks.
Cedar 14" dia., (now 24") N.78°W., 25 lks.
Set 1" iron pipe with a brass cap, stamped "COUNTY SURVEYORS OFFICE ¼ S23 24"

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - July 28, 1981 - C.S. File 61/27-26

Found - Brass Cap, firmly set, protruding 6" out of the ground & mkd: County Surveyors Office ¼ S 23 24
36" Fir (Orig. 18"), alive, with well healed blaze, bears N.43°E., 19.1 ft. (Rec 18.5 ft.).
26" Cedar (Orig. 14"), now a snag, 7 ft. tall, hollow & burned with no face visible, bears N.78°W., 18.0 ft. (Rec 16.5 ft.) Ground is very steep which could account for the discrepancy in the distances.
New BTs- 6" Fir bears S.26°E., 20.7 ft., scribed ¼ S24 BT
10" Fir bears N.13°E., 9.2 ft., scribed ¼ S23 BT
7" Fir bears N.45°W., 18.9 ft., scribed ¼ S23 BT
Note - All new BTs scribed on double blazes.
All BTs have DCSO BT tags.

Dependent resurvey by Boyd W. Peterson & Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May-Sept. 1985 - (DCSO rec Vol. 48 Pgs 18207)

The ¼ sec. cor. of secs. 23 & 24, perpetuated and recorded by Irving, in 1947, further perpetuated and recorded by Quibell, in 1981, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees
A fir, 36" dia., bears N.43°E., 28 lks., with healed blaze.
A cedar snag, 28" dia., bears N.78°W., 25 lks., with healed blaze.
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Quibell

A fir, 7" dia., bears S.27°E., 31 lks., with scribe marks
¼ S24 CS BT on partially healed blaze.

A fir, 9" dia., bears N.45°W., 28½ lks., with scribe marks
S23 BT visible on partially healed blaze.

A fir, 12" dia., bears N.13°W., 14 lks., with fragmentary
scribe marks visible on pitched over blaze.

Ronald L. Rice, Ward NW - For: Seneca Jones Co. - April 2011
- M162-30

Found - 1947 Douglas County brass cap with the following
accessories:

20" D.Fir bears N.13°W., 9.2' - Healed face

15" D.Fir bears N45°W 18.8' - Healed face

10" D.Fir bears S27°E 20.5' - Healed face

36" D.Fir snag bears N43°E 18.5' - Healed face

22" W. Red Cedar staub bears N78°W 16.5' - Healed
face.