

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4991)

Set oak post, 3 ft. long, 4" sq., firmly in the ground for ¼ sec. cor. mkd ¼ S on E & W faces, from which
 A fir, 32" dia., bears N.45°W., 30 lks., mkd: ¼ S BT.
 A fir, 36" dia., bears S.50°E., 29 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Ben B. Irving, County Surveyor - Witnesses: H.C. Carey & R.C. Kerchner - March 29, 1945 - C.S. File 38/46

Set stone 8x14x24" marked ¼ S on face. Remarkd 0BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - 11/6/1968 - C.S. File 54/40-103

Found - Mound of Stone but no marked stone as called for in 1945 Ren.
 Orig. 32", now 48" Fir, alive, N.45°W. 19.8 ft., bark scribed.
 Orig. 36", now 52" Fir, alive, S.50°E. 19.1 ft., frag. bark scribe.
Set - Brass Cap at Cor. mkd: County Surveyors T27S R3W Office, 1968 ¼ S14|S 13
New BTs- 8" R.Fir S.27°E., 10.5 ft. mkd: ¼ S13 CS BT
 8" R.Fir N.57°W., 7.0 ft. mkd: ¼ S14 CS BT
This corner lies on moderate SW slope approx. 200 ft. S. of Wolf Creek access road.

Fd. BC W. Rogers, 8/2001 - 2001-0092A&B

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 2/7/2021 - C.S. File 67/49-12

Found - A 1" i.d. iron pipe by Tracy, in 1968, firmly set, projecting 5" above the ground in a 12" dia. x 6" buried mound of stone with a 2½" dia. brass cap (properly) marked.
 The monument was found leaning 0.4 ft, ESE and was straightened to a plumb position.
 Original BTs by Flint 1882
 A 42" dia. x 3' tall D.Fir stump with a metal cap bears S.55°E., 21.3 ft. (Rec. S.50°E., 29 lks. to face)
 A 48" dia. x 25' tall D.fir snag bears N.45°W., 19.8 ft. with illegible bark scribing.
Continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BTs by Tracy in 1968 -
A 20" dia. W.Fir bears S.27°W., 10.5 ft. with a healed blaze.
A 13" diam. W.Fir bears N.63°W., 7.0 ft. with a healed blaze. (Rec. N.57°W.)
New BT - A 5" dia. D.Fir bears N.15½°E., 15.8 ft. scribed "X" & "BT" on a double blaze.
Note - The corner falls on a moderate SW slope approximately 200 ft. south of USBLM Wolf Creek Access Road.
All BTs have BT Tags attached. All new BTs have double blazed faces . All bearings are measured to the center of the trees at the root crown and distances measured to a 4" MAGHUB nail in the side and center of the root crown.
Geodetic coordinates - no GPS signal avail.
Compass declination: 14¾°E.