

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4991-2)

-----  
Cor. to secs. 11, 12, 13, & 14, on summit of ridge, course N & S. Set Laurel post, 4 ft. long, 4" sq., firmly in ground, mkd: T27S R3W S12 on NE, S11 on NW, S14 on SW, & S13 on SE faces, with 4 notches on the S & 1 on the E edges, from which  
A fir, 24" dia., bears N.48°E., 109 lks., mkd: T27S R3W S12 BT.  
A B.Oak, 20" dia., bears N.5°W., 54 lks., mkd: T27S R3W S11 BT.  
A laurel, 36" dia., bears S.10°W., 32 lks., mkd: T27S R3W S14 BT.  
A B.Oak, 12" dia., bears S.83°E., 15 lks., mkd: T27S R3W S13 BT.

Douglas Co. Surveyors Office - Ben B. Irving, County Surveyor - Witnesses: H.C. Carey & R.C. Kerchner - March 29, 1945 - C.S. File 38/46

-----  
Location identified from OBT  
Set stone 8x8x20" 10" in ground for cor.  
60" Fir N.46°45'E., 71.9 ft.  
32" Fir S.72°23'E., 90.0 ft.  
16" Fir N.54°45'W., 16.0 ft.  
10" Fir S.10°22'W., 12.4 ft.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12416-7)

-----  
The corner of secs. 11, 12, 13, & 14, perpetuated & recorded by Irving, in 1945, monumented with a stone, 20x8x8", firmly set, 8" above ground, with 5 grooves on the W and 2 grooves on the N face, from which the original bearing trees:  
A fir, 45" dia., bears N.45½°E., 109 lks., bark scribed T27S R3W S12 CS BT. (Record bearing N.48°E.)  
A madrone, 50" dia., bears S.10°W., 32 lks., with a partially opened blaze, no scribe marks visible.  
The stump hole and roots of a black oak, bears N.5°W., 54 lks.  
and the county surveyor's bearing trees:  
A fir, 37" dia., bears S.72½°E., 136 lks. bark scribed TS27 R3W S13 CS BT.  
A fir, 13" dia. bears S.10½°W. 19 lks. with a healed blaze  
A fir, 17" dia. bears N.54¾°W. 24 lks. with a healed blaze  
At the corner point  
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

T27S R3W  
S 11 | S 12  
S 14 | S 13  
1958

from which

A fir, 7" dia. bears N.61½°E. 46 lks. mkd: T27S R3W S12 BT  
A fir, 7" dia. bears S.40¼°E. 65 lks. mkd: T27S R3W S13 BT  
A fir, 8" dia. bears S.64°W., 6 lks., mkd: T27S R3W S14 BT  
A fir, 13" dia. bears N.11¼°W. 13 lks mkd: T27S R3W S11 BT  
Deposit local corner material alongside iron post.

Fd. & used on BLM dependent resurvey by Lance J. Bishop & Wayne L. Rogers, Cadastral Surveyors, under Group #1189, surveyed May/July 1984 - (DCSO records Vol. 47 Pages 17953-4)

FD. BC & BTs by Ronald G. Geisler, 2/25/1986 - C.S. 63/34-22