

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4971)

Set post for cor. to secs. 1, 2, 11, & 12, from which
A maple, 10" dia., bears S.45°E., 30 lks.
A fir, 18" dia., bears S.40°W., 40 lks.
A laurel, 12" dia., bears N.40°W., 55 lks.
A fir, 12" dia., bears N.40°E., 44 lks.

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4993)

Cor. to secs. 1, 2, 12, & 11, from which post
A fir, 12" dia., bears N.40°E., 44 lks., mkd: T27S R3W S1 (on NE) BT.
A laurel, 12" dia., bears N.40°W., 55 lks., mkd: T27S R3W S2 BT.
A fir, 18" dia. bears S.40°W. 40 lks mkd: T27S R3W S11 BT
A maple, 10" dia., bears S.45°E., 30 lks., mkd: T27S R3W S12 BT.

Arthur Boyer, DCS - Witnesses: N.E. Richardson, Jno. LaBonte & O.J. Noice - March 1936 - C.S. File 23/35

Found trees in NE Sec. & SW Sec. 11 quadrants OK but scribe marks gone so that they are hard to read but could be identified so renewed scribe marks on these trees. Fd. Laurel, gone Sec. 2 except stump so renewed it: Maple in Sec. 12 gone renewed for this quadrant. Set Fir post & set pole of rocks for corner from which
Cedar 8" dia., bears N.58½°W., 12.5 ft.
Maple 14" dia., bears East 48.7 ft.

Douglas Co. Surveyors Office - Ben B. Irving, County Surveyor - Witnesses: H.C. Carey & R.C. Kerchner - March 15, 1945 - C.S. File 38/46

As described by Boyer & recorded - Cedar in Sec. 2 broken off, OBT Sec. 1 will burn out.
Marked - Yew 8" N.49°W., 39.7 ft.
Fir 36" N.68°E., 29.8 ft.

continued next page

1

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12418-9)

The cor. of secs. 1, 2, 11, & 12, perpetuated with a wooden stake, 3x3" cross section, firmly set, 24", above ground, at record bearing and distance from the only remaining original bearing tree:

A down fir, 14" dia., bears N.40°E., 44 lks., with a partially opened blaze, and county surveyor's bearing trees:

A maple, 14" dia., bears E., 73 lks., with a healed blaze.

A yew, 8" dia., bears N.49°W., 60 lks. with scribe marks T27S R3W S2 CS BT visible on opened blaze. cont next pg

At the corner point

Set an iron post, 28" long, 2½" dia., 20" in the ground and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T 27 S R 3 W

S 2 | S 1

S 11 | S 12

1958

from which

A fir, 13" dia. bears N.30°E. 158 lks. mkd. T27S R3W S1 BT

A maple, 13" dia., bears S.60°E., 160 lks., mkd: T27S R3W S12 BT.

A fir, 6" dia. bears S.76°W. 132 lks. mkd: T27S R3W S11 BT

A fir, 7" dia., bears N.7½°W., 68 lks. mkd: T27S R3W S2 BT

Deposit local corner material alongside iron post.

Fd. Ok 2/1986, M100-48 - R. Gesisler.

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1101 surveyed Sept. 1982/May 1983 - (DCSO records Vol. 46 Page(s) 17506)

The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd., from which the remains of an original bearing tree

A decayed fir stump, 14" dia., bears N.38°E., 48 lks., with axe marks visible on decayed blaze. (Record, N.40°E., 44 lks.)

and a BT mkd. by Boyer, Deputy County Surveyor, in 1936

A maple, 17" dia., bears N.85½°E., 78 lks., with healed blaze. (Record, East, 73 lks.)

and a BT mkd. by Irving, Deputy County Surveyor, in 1945 continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A yew, 13" dia., bears N.47°W., 60 lks., with fragmentary scribe marks visible on partially healed blaze. (Record, N.49°W.)
and bearing trees mkd. by Corbin
A fir, 18" dia., bears N.30°E., 158 lks. with healed blaze
A maple, 18" dia. bears S.60°E., 162 lks. with fragmentary scribe marks visible on partially healed blaze. (Rec. 160 lks.)
A fir, 15" dia., bears S.76°W., 130 lks., with healed blaze. (Record, 132 lks.)
A fir, 13" dia., bears N.6°W., 68 lks., with healed blaze. (Record, N.7½°W.)

Fd. Ok by Ron Quimby 5/2005 - M147-62