

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600620

PRIMARY CORNER DESCRIPTION S 1/16 Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Arthur Boyer, DCS - Witnesses: N.E. Richardson, Jno. LaBonte & O.J. Noice - March 1936 - C.S. File 23/35

-----  
Set Fir post & pile of rocks for corner from which  
An Oak stump 12" dia., bears S.80½°W., 70.9 ft.  
A Pine stump 36" dia., bears N.37½°E., 84 ft.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12421)

-----  
Point for the S 1/16 sec. cor. of secs. 1 & 2  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:  
S 1/16  
S 2|S 1  
1958

from which  
A W.Oak, 14" dia. bears S.77½°E. 257 lks. mkd: S1/16 S1 BT  
A pine, 6" dia. bears S.41½°W., 177 lks., mkd: S1/16 S2 BT

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1101 surveyed Sept. 1982/May 1983 - (DCSO records Vol. 46 Page(s) 17506-7)

-----  
The S 1/16 sec. cor. of secs. 1 & 2, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.,  
from which the remains of bearing trees mkd. by Corbin  
A W.Oak, 21" dia., bears S.77½°E., 257 lks., with healed blaze.  
A pine snag, 17" dia. S.41½°W., 177 lks. with healed blaze and new BTs  
A fir, 7" dia., bears S.77½°E., 118 lks. mkd: S 1/16 S1 BT  
A pine, 6" dia., bears S.43°W., 33 lks., mkd: S 1/16 S2 BT