

PRIMARY CORNER DESCRIPTION 1/4 Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4971)</p> <p>-----</p> <p>Set post for ¼ sec. cor. from which A pine, 26" dia., bears S.80°W., 24 lks. A W.Oak, 6" dia., bears N.15°E., 91 lks.</p>
<p>Arthur Boyer, DCS - Witnesses: O.J. Noice, N.E. Richardson, T.V. Gurnee & Jno. LaBonte - March 1936 - C.S. File 23/35</p> <p>-----</p> <p>Identified location from Oak stump the tree of which has been burnt. Jno. LaBonte & T.V. Gurnee testify that this is the orig. BT for Sec. 1. Set fir post & pile rocks for corner from which A 40" bark blazed Fir bears N.51°E., 80.0 ft. A 40" barks blazed Fir bears S.63°W., 46.2 ft.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - R. Irving & John Fee - April 1954 - C.S. File 46/20</p> <p>-----</p> <p>Found - 3" by 3" scribed post & 5/8" IP. Old BT (snag) scribe visible, N.50°40'E., 80 ft. Set - Brass disk. Blazed & scribed 40" fir (snag) S.61°W., 48.0 ft., mkd ¼ S2 CS BT. Set brass disk Red Butte lookout bears S.48°E. Old fence corner bears N.74½°W., 6.0 ft.</p>
<p>BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12421-2)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 1 and 2, perpetuated and recorded by County Surveyor Boyer at record bearing and distance from the original NE. bearing tree, which is no longer in existence, monumented with an iron pipe, ¾" dia., firmly set, 12" above ground, and in a mound of stone, 2½ ft. base, to top, from which the county surveyor's bearing trees; A fir stump, 40" dia., bears N.51°E., 121 lks., bark scribed ¼ S1 BT. A fir snag, 40" dia., bears S.63°W., 70 lks., with scribe marks ¼ S2 CS BT visible on opened blaze. At the corner point Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap mkd. T27S R3W ¼ S2 S1 1958</p> <p style="text-align: right;">continued next page</p>

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit local corner material alongside iron post & raise a mound of stone, 2½ ft. base, 1½ ft. high W. of corner.

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1101 surveyed Sept. 1982/May 1983 - (DCSO records Vol. 46 Page(s) 17507)

The ¼ sec. cor. of secs. 1 and 2, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Boyer, in 1936
A sawed fir stump, 40" dia., bears N.51°E., 121 lks. with fragmentary scribe marks visible on bark blaze.
A fir snag, 40" dia., bears S.63°W., 70 lks. with scribe marks BT visible on opened blaze.
and new bearing trees
A fir, 6" dia., bears N.3¼°E., 78 lks., mkd. ¼ S1 BT.
A fir, 10" dia., bears S.75°W., 34 lks., mkd. ¼ S2 BT.

Ronald Quimby - For: Roseburg Resources - May 2005 - M147-62

Found - 1958 BLM BCIP, properly marked.
19" Fir bears N.3°E., 51.8 ft., healed scar.
26" Fir bears S.75°W., 22.4 ft., healed scar.
40" Fir stump N.51°E., 80.7 ft. (1954)
New BTs- 8" Fir bears S.52°E., 22.9 ft. scribed ¼ S1 BT.
6" Fir bears N.5°W., 13.8 ft. scribed ¼ S2 BT.