

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4987)

Set cedar post, 3 ft. long, 4" sq., firmly in the ground for 1/4 sec. cor. mkd on N & S faces, 1/4 S, from which
A fir, 12" dia., bears S.30°E., 6 lks., mkd: 1/4 S BT.
A fir, 20" dia., bears N.62°W., 31 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John Powell - July 30, 1970 - C.S. File 54/40-190

Reported as not found.
Found large fir stump out of ground with 1952 tag saying this was BT, no evidence of scribing or other BTs. This cor. falls in old unit along old rd, probably old Rd took out BTs.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22040)

The 1/4 sec. cor. of secs. 25 and 36, determined at record bearing and from the remains of an original bearing tree
A sawed fir stump, 41" dia., bears N.62°W., 20.5 ft., with fragmentary scribe marks and axe marks visible on the bark.

At the corner point
Set a stainless steel post, 2 1/2" long, 28" dia., 24" in the ground, with brass cap mkd.

T 27 S R 3 W

1/4 $\frac{S\ 25}{S\ 36}$

2003

from which new bearing trees
A fir, 20" dia., bears N.78 1/2°E., 17.7 ft., mkd. 1/4 S25 BT.
A fir, 11" dia., bears S.26 1/2°E., 13.4 ft., mkd. 1/4 S36 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.