

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4994)

Set chincapin post, 3 ft. long, 4" sq., firmly in the ground, mkd on N & S faces, 1/4 S, from which

A cedar, 36" dia., bears S.25°E., 25 lks., mkd: 1/4 S BT.

A cedar, 36" dia., bears N.60°W., 64 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12420)

The 1/4 sec. cor. of secs. 1 & 12, perpetuated with a truck axle, 2" dia., firmly set, 4" above ground, at record bearing & dist. from orig. BTs:

A cedar stump, 36" dia., bears N.60°W., 64 lks., no marks visible.

A cedar stump, 36" dia., bears S.25°E., 25 lks., with old axe marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap marked:

T27S R3W

1/4 S 1

S 12

1958

from which

A fir, 10" dia., bears N.43 1/4°E., 92 lks., mkd: 1/4 S1 BT.

A fir, 8" dia., bears S.44°E., 100 lks., mkd: 1/4 S12 BT.

Deposit axle alongside iron post.

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1101 surveyed Sept. 1982/May 1983 - (DCSO records Vol. 46 Page(s) 17504-5)

The 1/4 sec. cor. of secs. 1 & 12, monumented with an iron post, 2 1/2" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.,

from which the remains of the original bearing trees

A sawed cedar stump, 36" dia., bears S.25°E., 28 lks., no marks visible. (Record, 25 lks.)

A sawed cedar stump, 36" dia., bears N.60°W., 60 lks., no marks visible. (Record, 64 lks.)

and bearing trees mkd. by Corbin

A fir, 12" dia. bears N.43 1/4°E., 92 lks., with healed blaze

A grand fir, 14" dia., bears S.44°E., 100 lks. with healed blaze.

continued next page

