

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 640640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1101 surveyed Sept. 1982/May 1983 - (DCSO records Vol. 46 Page(s) 17508)

Point for the center ¼ sec. cor. of sec. 1, at intersection with the E and W center line.

Set an aluminum post, 28" long, 2½" dia., 24" in the ground, with aluminum cap mkd. T27S R3W
C 1/4 S 1
1982

from which

A fir, 17" dia., bears S.9°E., 20½ lks., mkd. C ¼ S1 BT.

A maple, 10" dia., bears N.16½°W., 30 lks. mkd. C ¼ S1 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500 Admin. file 1104, Surveyed Aug/Oct. 2011 - (DCSO records BLM Plat 2012-1, T27-3 and Vol. 58 Page(s) 22911-2)

The center ¼ sec. cor. of sec. 1, monumented with on aluminum post, 2½" dia., firmly set, projecting 6" above ground. with aluminum cap (properly) mkd.

from which the bearing trees mkd. by Jelley and Rogers

A fir, 26" dia., bears S.9°E., 13.5 ft., with a healed blaze.

A maple, 15" dia., bears N.16½°W., 19.8 ft., with a healed blaze.