

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
(DCSO records Vol. 12 Page(s) 4862) and (Dup. Pg. #4984)

Set Cedar post 3 ft. long, 4" sq., firmly in the ground for
¼ sec. cor. mkd. on E. and W. faces ¼ S from which
 A Fir 20" dia., bears S.62°W., 13 lks. dist. mkd. ¼ S BT
 A Fir 20" dia., bears N.40°E., 32 lks. dist. mkd. ¼ S BT

Tied corner in GLO Resurvey by Morris Wygant, Compassman for
Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779,
dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4911)

Survey by Ronald G. Geisler - For: Champion International Co.
June/Aug. 1985 - M 90-71

(Witness corner)
Set a 2½" alum. cap on a 2½" x 30" alum. flared pipe, mkd.
PLS 1988.
BTs- 8" Fir bears N.28°W., 12.6 ft. scribed X BT.
 10" Fir bears N.81°E., 32.2 ft. scribed X BT.
The True Corner position falls in an existing dirt road. The
witness cor. bears S.00°44'16"W., 51.09 ft. from the true
point.