

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 25 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4861) and (Dup. Pg. 4984)

Set Cedar post 3 ft. long, 4" sq., firmly in the ground for 1/4 sec. cor. marked 1/4 S on E. and W. faces, from which
A Hemlock 10" dia., bears N.82°E., 13 lks. dist. mkd. 1/4 S BT.
A Fir 40" dia., bears S.65°W., 48 lks. dist. mkd. 1/4 S BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4911)

The 1/4 sec.cor. which is a post firmly set, marked and witnessed as described by the Surveyor General and which I now change to refer to secs. 25, T27S R3W only.

Survey by Ronald G. Geisler - For: Champion International Co. June/Aug. 1985 - M 90-71

Set a 2 1/2" aluminum cap on a 2 1/2" x 30" alum., flared pipe mkd. PLS 1988., from which
2" Hemlock bears N.88°W., 11.1 ft. scribed X BT.
3" Fir bears S.18°W., 19.2 ft. scribed X BT.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22034)

The 1/4 sec. cor. of sec. 25 only, reestablished by proportionate measurement by Geisler, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2" dia., firmly set, projecting 5" above the ground, with aluminum cap (properly) mkd.
from which bearing trees mkd. by Geisler
A fir, 9" dia., bears S.16 1/2°W., 19.1 ft., with a healed double blaze.
A hemlock, 5" dia., bears N.89 1/4°W., 10.9 ft., with a healed double blaze.