

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 700336


PRIMARY CORNER DESCRIPTION W 1/4 Cor. Sec. 19 only; T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22037)

Point for the ¼ sec. cor. of sec. 19 only, T. 27 S., R. 2 W., determined at midpoint latitudinally bet. the closing cor. of secs. 19 and 30, and the closing cor. of secs. 18 and 19.

Set a stainless steel post, 28 ins. long, 2½" dia., 23 ins. in the ground, with brass cap mkd.



from which

A cedar, 9" dia., bears N.59¼°E., 30.2 ft., mkd. ¼ S19 BT.

A fir, 16" dia., bears S.53½°E., 30.2 ft., mkd. ¼ S19 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located 17.0 ft. E. of an overgrown graveled road, 20 ft. wide, which bears N. 35° E. and S. 55° W.