

PRIMARY CORNER DESCRIPTION E. ¼ cor. Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4860) and (Dup. Pg. #4983)

set Cedar post 3 ft. long, 4" sq., for ¼ sec. cor. firmly in the ground marked ¼ S on E. and W. faces, from which

A Hemlock 36" dia., bears N.82°E., 33 lks. dist. mkd. ¼ S BT.

A Cedar 10" dia., bears N.20°W., 32 lks. dist. mkd. ¼ S BT

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4912)

The ¼ sec. cor. which is a post firmly set, marked and witnessed as described by the Surveyor general, and which I now change to refer to sec. 24, T27S R3W only.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/40-3

Looked for, not found.
 Found possible Cedar BT, scribe appears redone on burned face. No Hemlock to NE. Find D.Fir, bark badly burned.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22038)

Point for the ¼ sec. cor. of sec. 24 only, determined by the Broken Boundary Method. There is no remaining evidence of the original cor.

Drive a finned aluminum rod, 72" long, ¾" dia., 68" in the ground, with aluminum cap mkd.

T 27 S

R3W	R2W
¼	
S 24	

2003

from which

An alder, 8" dia., bears S.45¾°W., 8.7 ft., mkd. ¼ S24 BT in the bark.

An alder, 6" dia., bears N.43¾°W., 5.7 ft., mkd. ¼ S24 BT in the bark.

Deposit a magnet in a white plastic case alongside the finned aluminum rod.
 Corner is located in a wet marshy area.