

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4958-59)

 At intersection point 670 lks. S.1°01'E. of cor. to secs. 13 & 24, Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 18 and 19 marked CC T27S R2W on E.; S18 on N.; and S19 on S. face, with 3 grooves on S. and 3 grooves on N. face, from which
 A Fir 24" dia., bears N.62°30'E., 5 lks. dist. mkd. T27S R2W S18 BT.
 A Fir 14" dia., bears S.8°30'E., 12 lks. dist. mkd. T27S R2W S19 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 29, 1966 - C.S. File 54/40-1

 Found - Very old scribed Cedar post, badly decayed.
 Orig. 14" now 16" W.Fir, alive, S.8½°E., 7.9 ft.
 Open and find scribe "R 2 W S"
 Orig. 24" now 25" W.Fir, alive, N.62½°E., 3.3 ft., shows good scar. We do not open.

Set Brass cap at cor. mkd: County Surveyors Office

R		T 27 S	R
3	CC	S 18	2
W		S 19	W

 1966

New BTs- 8" W.Fir N.50°E., 12.6 ft mkd. T27S R2W S18 CC CS BT
 5" W.Fir S.78°E., 12.5 ft mkd. T27S R2W S19 CC CS BT
 Brass cap set 12" in the ground with mound of stone 16" high.
 Corner lies on flat, approx. 440 ft. S. of standard corner.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22010)

 Set a stainless steel post, 28" long, 2½" dia., 21" in the ground, with brass cap mkd.

		T 27 S	
R 3 W		R 2 W	
		S 18	CC
		S 19	

 2003

from which
 A fir, 20" dia., bears N.29¼°E., 27.5 ft., mkd. T27S R2W S18 CC BT.
 A fir, 11" dia., bears S.64¾°E., 28.3 ft., mkd. T27S R2W S19 CC BT.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 700373

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, the original closing cor. of secs. 18 and 19, established by Wygant in 1911, remonumented by the Douglas County Surveyors Office in 1966, bears N.89°36'29"W., 58.35 ft., monumented with an iron post, 1½" dia., firmly set, projecting 12" above a mound of stone, 2½ ft. base, to top, with brass cap mkd. COUNTY SURVEYORS OFFICE T27S R CC S18 R 3 2 W S19 W 1966

from which the remains of the original bearing trees

A sawed and decayed fir stump, 17" dia., bears N.62½°E., 4.2 ft., with fragmentary scribe marks visible on a partially opened blaze. (Record, 3.3 ft.)

A decayed fir stump, size indeterminate, bears S.16¼°E., 6.9 ft., with fragmentary scribe marks T BT visible on a partially opened blaze. (Record, S.8½°W., 7.9 ft.)

There is no remaining evidence of the bearing trees mkd. by the Douglas County Surveyors Office in 1966, due to logging activity in this area.

Add the marks AM on the brass cap.