

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T27-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4858-59) and (Dup. pg. #4981)

Corner to secs. 12, 13, 7 and 18, at which a Cedar post 4 ft. long, 4" sq., firmly set in the ground and mkd. T27S R2W S7 on NE.; R3W S12 on NW.; R3W S13 on SW. and S18 on SE. faces, with 2 notches on North and 4 on S. edges, from which
A Hemlock 8" dia., bears N.48°E., 41 lks. dist. mkd. T27S R2W S7 BT.
A Hemlock 8" dia., bears N.42°W., 58 lks. dist. mkd. T27S R3W S12 BT.
A Fir 20" dia., bears S.60°W., 7 lks. dist. mkd. T27S R3W S13 BT.
A Fir 30" dia., bears S.58°E., 59 lks. dist. mkd. T27S R2W S18 BT.

Survey by Thomas E. Shrum, Jr. - For: U.S. Plywood Corp. - Jan. 1961 - C.S. File 51/174 and M 11-78

Found - 30" D.Fir, S.58°E., 38.9 ft., windthrown.
Set 3/4" x 36" Iron rod, from which
6" Cedar N.19°30'W., 45.7 ft.
24" D.Fir S.37°W., 81.7 ft.
18" D.Fir S.73°30'E., 35.8 ft.
8" Hemlock N.6°E., 45.4 ft.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #983, surveyed May/Aug. 1979 - (DCSO records Vol. 43 Page(s) 16911-12)

The Sec. Cor., perpetuated and recorded by Shrum in 1961, determined at record bearing and distance from the remains of the original bearing trees:
A root hole bears S.58°E., 59 lks. dist., with down Fir alongside 40" dia., with scribe marks T27S R W S18 BT visible on bark.
A root hole bears S.60°W., 7 lks. dist.
A root hole bears N.42°W., 58 lks. dist.
and bearing trees marked by Shrum:
A root hole bears N.1°E., 69 lks. dist. with down Hemlock alongside 14" dia., with illegible scribe marks visible on partially healed blaze.
A Fir 17" dia., bears S.71½°E., 54 lks. dist., with healed blaze and scribe marks BT visible on bark at base.
A root hole bears S.35½°W., 124 lks. dist., with down Fir alongside 30" dia., no marks visible.

(Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar stump 14" dia., bears N.23°W., 69 lks. dist., no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 27 S
R 3 W R 2 W
S 12 S 7
S 13 S 18
1979

from which new bearing trees

A Cedar 9" dia., bears N.17°E., 23 lks. dist. mkd. T27S R2W S7 BT.

A Hemlock 5" dia., bears S.31°W., 43 lks. dist. mkd. T27S R3W S13 BT.

A Hemlock 6" dia., bears N.66°W., 46 lks. dist. mkd. T27S R3W S12 BT.

Corner is located in the SE. cor. of a logged area.