

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; & 6 & 7, T27-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4857-58) (and dup. pg. #4980)

Set Oak post 4 ft. long, 4" sq., firmly in the ground and marked T27S R2W S6 on NE.; T27S R3W S1 on NW.; R2W S7 on SE.; R3W S12 on SW.; with one notch on the North and 5 notches on the S. edges, from which

- A Laurel 20" dia., bears N.33°E., 86 lks. dist. mkd. T27S R2W S6 BT.
- A Fir 6" dia., bears N.48°W., 80 lks. dist. mkd. T27S R3W S1 BT.
- A Laurel 15" dia., bears S.45°W., 175 lks. dist. mkd. R3W S12 BT.
- A Fir 6" dia., bears S.35°E., 35 lks. dist. mkd. R2W S7 BT.

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 412, Surveyed Aug/Nov. 1958 - (DCSO records Vol. 29 Page(s) 12419)

The Sec. Cor., determined at record bearing and distance from the only remaining original bearing tree, as follows:

- A Madrone 20" dia., bears S.45°W., 175 lks. dist. with scribe marks BT visible on a partially opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 27 S
R 3 W R 2 W
S 1 S 6
S 12 S 7
1958

from which

- A Fir 12" dia., bears N.40°E., 155 lks. dist. mkd. T27S R2W S6 BT.
- A Fir 12" dia., bears S.57°E., 87 lks. dist. mkd. T27S R2W S7 BT.
- A Fir 15" dia., bears S.60°W., 36 lks. dist. mkd. T27S R3W S12 BT.
- A Fir 10" dia., bears N.35½°W., 34 lks. dist. mkd. T27S R3W S1 BT.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #983, surveyed May/Aug. 1979 - (DCSO records Vol. 43 Page(s) 16914)

The Sec. Cor., monumented with an iron post 2½" dia., firmly set, projecting 2" above ground with brass cap mkd in 1958, (Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T27-2

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

from which the remains of bearing trees mkd. by Corbin:
A sawed Fir stump 20" dia., bears N.40°E., 155 lks. dist., with healed blaze.
A Fir 11" dia., bears S.55°E., 95 lks. dist. with healed blaze. (Rec. S.57°E., 87 lks.)
A Fir 20" dia., bears S.60°W., 36 lks. dist. with healed blaze.
and new bearing trees
A Fir 10" dia., bears N.15°E., 137 lks. dist. mkd. T27S R2W S6 BT.
A Pine 33" dia., bears N.15°W., 61 lks. dist. mkd. T27S R3W S1 BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1093, surveyed Sept/Oct. 1982 - (DCSO records Vol. 45 Page(s) 17501)

The Sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. in 1958, from which the remains of bearing trees mkd. by Corbin:
A Fir 13" dia., bears S.55°E., 95 lks. dist., with healed blaze.
A sawed Fir stump 24" dia., bears S.60°W., 36 lks. dist., with healed blaze.
and a bearing tree mkd. by Rogers:
A Pine 34" dia., bears N.15°W., 61 lks. dist., with scribe marks T27S R3W S1 BT visible on open blaze.
and new bearing trees:
A Fir 13" dia., bears N.12°E., 220 lks. dist., mkd. T27S R2W S6 BT.
A Fir 4" dia., bears S.22½°W., 30½ lks. dist. mkd. X BT.