

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & S. 6, T27-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4857) (and dup. pg. #4980)

Set Chinquapin post 3 ft. long, 4" sq., firmly in the ground for 1/4 sec. cor. marked on E. and W. faces, 1/4 S., from which
A Laurel 5" dia., bears N.15°W., 36 lks. dist. mkd. 1/4 S BT
A Fir 36" dia., bears N.35°E., 42 lks. dist. mkd. 1/4 S BT.

BLM Corner Remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 412, Surveyed Aug/Nov. 1958 - (DCSO records Vol. 29 Page(s) 12443)

The 1/4 sec. cor., determined at record bearing and distance from the two original bearing trees:

- A Fir 55" dia., bears N.35°E., 42 lks. barks scribing 1/4 S.
- A rotted Madrone stump, bears N.15°W. 36 lks no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 27 S
R 3 W 1/4 R 2 W
|
S 1 | S 6

1958

from which

- A Fir 18" dia., bears S.62°E., 36 lks. dist. mkd. 1/4 S6 BT.
- A Cedar 6" dia., bears S.51°W., 45 lks. dist. mkd. 1/4 S1 BT

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16929)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1093, surveyed Sept/Oct. 1982 - (DCSO records Vol. 45 Page(s) 17501-02)

The 1/4 sec. cor., monumented with an iron post 2 1/2" dia., firmly set, projecting 4" above ground, with brass cap mkd. in 1958, from which the remains of an orig. bearing tree:

- A sawed Fir stump 59" dia., bears N.35°E., 42 lks. dist., with fragmentary scribe marks visible on bark blaze.
- and the remains of the bearing trees mkd. by Corbin:
- A sawed Fir stump 26" dia., bears S.62°E., 36 lks. dist., with healed blaze.
 - A Cedar 21" dia., bears S.51°W., 45 lks. with healed blaze

and a new bearing tree

- A Grand Fir 11" dia., bears N.19°E., 125 lks. mkd. 1/4 S6 BT