

TOWNSHIP 27 RANGE 04E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Township Corner

Alias _____ Description (Sec 31 T27-4E = PB 42)
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,
under special instructions dated Dec. 27, 1920, Surveyed Aug
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10484)

East on the S bdy of sec. 36 at 65.65 chs: Old standard cor.
of Ts. 27 S, Rs 3 & 4 E., bears N 4.29 chs. Now obliterated.
(See Flint 1883 survey Vol. 24 Pg. 10051) AT 80 chs:
Set an iron post, 3 ft. long, 3" dia., 27" in ground, for
standard cor. of Ts. 27 S., Rs. 3 & 4 E., with brass cap mkd.

S C
T27S
R3E|R4E
S 36|S 31
T28S R4E
S 6
1929

from which

- A fir, 34" dia., bears N.59°E., 23 lks., mkd: S C T27S R4E
S31 BT.
- A fir, 34" dia., bears N.31°W., 63 lks., mkd: S C T27S R3E
S36 BT