

TOWNSHIP 27 RANGE 04E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 30; 24, & 25 T27-3E

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10054)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T27S  
R3E|R4E  
S 24|S 19  
S 25|S 30  
1929

from which

- A fir, 14" dia., bears N.45°E., 54 lks., mkd: T27S R4E S19 BT.
- A fir, 30" dia., bears S.29°E., 26 lks., mkd: T27S R4E S30 BT.
- A fir, 18" dia., bears S.80½°W., 48 lks., mkd: T27S R3E S25 BT.
- A fir, 20" dia., bears N.50°W., 40 lks., mkd: T27S R3E S24 BT.