


TOWNSHIP 27 RANGE 04E POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7; & 12 T27-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10057)

-----  
Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked



from which

- A fir, 10" dia., bears N.83°E., 58 lks., mkd: 1/4 S7 BT.
- A fir, 8" dia., bears N.16 1/2°W., 73 lks., mkd: 1/4 S12 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton - May 12, 1977 - C.S. File 59/34-14

-----  
Found - 1929 GLO brass cap 4" above ground surface. Township & range not stamped on brass cap. (T27S on line between R3E & R4E)

A 23" Fir stump bears N.16 1/2°W., 48.3 ft. No scribing or face (Stump cut short). (Rec. N.16 1/2°W., 48.18 ft.)

A 17" Fir stump bears N.83°E., 38.28 ft. No scribing or face. (Stump cut short, close to ground).

New BTs- A 15" D.Fir bears N.85 1/2°E., 51.3 ft. scribed "1/4 S7 CS BT" on a double blaze.

A 20" D.Fir bears S.58°W., 84.5 ft. scribed "1/4 S12 CS BT" on a double blaze.

County BT tags placed on both.

Note - Corner lies 200 ft. West of F.S. Rd. #2734 in a partial cut unit.