

TOWNSHIP 27 RANGE 04E POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Township corner

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10059)

-----  
Set an iron post, 3 ft. long, 3" dia., 30" in the ground, for cor. of Ts. 26 and 27S., Rs 3 and 4E, with brass cap mkd:

T26S  
R3E|R4E  
S 36|S 31  
S 1|S 6  
T27S  
1930

from which

- A fir, 36" dia., bears N.68°E., 27 lks., mkd: T26S R4E S31 BT.
- A madrona, 7" dia., bears S.62°E., 39 lks., mkd: T27S R4E S6 BT.
- A cedar, 12" dia., bears S.5°W., 30 lks., mkd: T27S R3E S1 BT.
- A fir, 36" dia., bears N.85°W., 92 lks., mkd: T26S R3E S36 BT.