

PRIMARY CORNER DESCRIPTION NW Cor. Matthews DLC #43

Alias	Description

<p>Original - Aaron Bowser, Contract dated April, 1856 Survey approved 1858</p> <p>-----</p> <p>Set post, from which A B.Oak 12" dia. bears S.57°E., 83 lks. Raised mound with trench as per instructions.</p>
<p>Volume 2 Page 265 by (?) date (?)</p> <p>-----</p> <p>Set Oak stake 4" x 4" x 3 ft. for NW Cor. Cl. 43 Old BTs in evidence. B.Oak 26" dia. bears N.79°W., 50 lks. dist. B.Oak 20" dia. bears S.59°45'W., 60 lks. dist.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone January 1964 - C.S. File 53/33-50</p> <p>-----</p> <p>Found - 34" B.Oak N.79°W., 33.0 ft. This tree has been opened years ago, face badly rotted, no scribing found, but portions of overgrowth on flat face found. Badly rotted Oak stump S.59¾°W., 39.6 ft., showed axe marks on surface, no scribing found. Large stump hole S.57°E., 54.8 ft. (This fits original BT) Remains of old N & S fence meets present E & W fence 4 ft. South of corner. Set brass cap at cor. mkd: County Surveyor's Office 1964 T27S R4W /DLC 43 New BTs - 7" D.Fir S.11°W., 8.5 ft. mkd: "NW DLC 43 CS BT". 5" D.Fir N.61°E., 63.0 ft. mkd: "NW DLC 43 CS BT".</p>
<p>Found OK, per Donald Bentz, October 1987, M 105-42</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/20/2000 - C.S. File 66/16-43</p> <p>-----</p> <p>Found - 1964 DCSO brass cap iron pipe, protrudes 9" above ground in a E-W fence line. 7" now 19" dia., D.Fir with a fully healed single blaze, bears S.11°W., 8.5 ft. (1964) 5" now 16" dia., tagged down D.Fir in slide area, fd. approx. North 15 ft. of rec. (N.61°E., 63.0) has no position . (1964) 26" now large down B.Oak in slide area root hole bears N.79°w., 33.0 ft. No other BTs found. continued next page</p>

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 043020

PRIMARY CORNER DESCRIPTION NW Cor. Matthews DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 13" dia., D.Fir double blazed & scribed "NW DLC 43 CS BT" bears N.78°E., 87.7 ft. (approx. 15 East of Easterly edge of slide)
14" dia. D.Fir double blazed & scribed "NNW DLC 43 CS BT" bears S.83°W., 83.4 ft. (15' W of W'ly slide)

Note - Corner lies in an island of land between land slides East & West of corner New BTs marked outside of present slide boundaries
(DLC corner on 7.5 min. topo positions corner approx. 275 ft. east of found corner.