

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 043030

PRIMARY CORNER DESCRIPTION SW Cor. Matthews DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Aaron Bowser, Contract dated April 4, 1856
Survey approved, 1858

Set post in prairie, from which
 A W.Oak 20" dia. bears N.88°E., 328 lks.
 Raised mound with trench as per instructions.

William P. Heydon, Co. Surveyor - For: L.L. Mathews
August 9, 1894 - Volume 2 Page 35

I begin at the SW cor. which I establishe from notes made by
Wm. Theil, Co. Surveyor in 1872 (Record Source ?)
From the witness tree, I establish said corner S.89°45'E.,
1 ch. 13 lks. I also mark new witness tree:
 A Madrona, 14" dia. bears S.42°W., 12 lks.

G.G. Stewart, D.C.S. Wit: Red Mathews; Shelby Mathews; W.S.
Crear - June 26, 1922 - C.S. File 4/1

Reset from old BT, a Laurel that has been cut and was rotten.
Set an Iron pipe for corner and marked the following trees:
 W.Oak 24" dia. bears S.85°W., 74.5 ft.
 Remarked Old BT, Laurel, 14" stub, S.40°W., 8 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone
November 1963 - C.S. File 53/33-45

Found - 35" W.Oak S.85°W., 74.5 ft. Cut open scar & found
 good reverse. Tree rotting badly inside, nearly
 hollow.
 28" Laurel S.40°W., 8.0 ft. Old face rotted away.
Set brass cap at cor. mkd. County Surveyor's Office 1963
 T27S R4W SW D.L.C. No. 43 | _____
New BTs - 11" W.Oak S.44°E., 15.5 ft. mkd: SW DLC 43 CS BT.
 7" W.Oak N.78°W., 33.8 ft. mkd: SW DLC 43 CS BT.
Corner is approx. 8 ft. North of E & W fence line in edge of
cultivated field.