

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION S SE Cor Matthews DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Aaron Bowser, Contract dated April 4, 1856
Survey approved, 1858

Set post, from which
 A B.Oak 15" dia. bears N.46°W., 82 lks.
 A B.Oak 14" dia. bears N.45°E., 50 lks.

William P. Heydon, Co. Surveyor - L.L. Mathews - Aug. 9, 1894
Volume 2 Page 35

Set a White Oak post for corner from which
 A Limb, 8" on a fallen Maple bears N.13°W., 77 lks.

G.G. Stewart D.C.S. - Shelby Matthews; Red Matthews; W.S.
Crear, June 6, 1922 - (Record source not found, See "Old"
Corner renewal book, Page 84)

Reestablish from 8" limb on Maple, old BT.
Set Iron pipe for corner and mark:
 20" Fir N.28°E., 10½ lks.
 6" W.Oak N.63°W., 32 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone
November 1963 - C.S. File 53/33-46

Found - ½" Iron pipe set in 1922.
 Stump of 20" Fir N.28°E., 7.0 ft., cut open & found
 good scribing.
 8" W.Oak N.57°W., 18.7 ft. (Rec. calls for N.63°W.,
 21.1 ft.) Reblaze & scribe this tree "SE DLC
 43 CS BT".
New BT - 9" Maple S.50°W., 20.2 ft. mkd: SE DLC 43 CS BT.
Corner is in N & S fence line.