

PRIMARY CORNER DESCRIPTION E NE Cor Cooc DLC #44

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Aaron Bowser, Contract dated April 4, 1856 Survey approved, 1858</p> <p>-----</p> <p>Set post, from which A B.Oak 14" dia. bears S.40°W., 34 lks. Raised mound with trench as per instructions.</p>
<p>G.G. Stewart, D.C.S. - Wit: Red Matthews; Shelby Matthews W.S. Crear - June 26, 1922 - C.S. File 4/1; & "Old" cor. Book, Page 84</p> <p>-----</p> <p>Reestablished from dead O.B.T. Set Iron pipe for corner and marked the following trees: W.Oak 6" dia. bears S.15½°W., 6.8 ft. 18" B.Oak S.75½°E., 53.5 ft.</p>
<p>A. Boyer; N.E. Richardson - March 22, 1936 (Record source not found) See "Old" Corner Renewal Book, Page 84 and 85</p> <p>-----</p> <p>The 6" W.Oak by Stewart has been cut down so the following tree was marked: 15" W.Oak N.59°E., 36 ft.</p>
<p>Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone - Nov. 1963 C.S. File 53/33-48</p> <p>-----</p> <p>Found - ½" Iron pipe set by Stewart in 1922. Stump of 15" W.Oak N.59°E., 36.0 ft. scribing visible "C". No trace of either of other 2 bearing trees. New BTs - 8" W.Oak S.2°W., 66.8 ft. mkd. NE DLC 44 CS BT. 4" B.Oak N.56°E., 29.8 ft. mkd: DLC 44 CS BT.</p>
<p>Greg Lang, 4/2013, M165-13: fd 10 W.Oak BT (S.2°W. 66.80') Corner buried in deep fill material (location calc from fd BT)</p>
<p> </p>