

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 046030

PRIMARY CORNER DESCRIPTION SW Cor. Thomas Anderson DLC 46

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Aaron Bowser, Contract dated April 6, 1856, Survey approved, 1858 - (DCSO DLC records page 374)

Set stone post in prairie 16x8. Raised mound with trench as per instructions.

Kris DeGroot - For: City of Roseburg - 4/2008 - M146-78

R. H. Gee set a 3/4" iron pipe under M 11-53 at the "Southerly end of an existing fence line testified to be on the west line of DLC No. 46 by a settler" The original 16"x8" stone and RM 1-44 3/4" iron pipe are missing. I computed the position of the 3/4" iron pipe proportionately between the fd RM1-44 5/8" iron rods and then excavate 24" to find the remains of a charred oak post and accept this position as the original SW corner of DLC No. 46. I then set a 1 1/2" x 30" iron post, 28" in ground with 2 1/2" brass cap stamped:

T27S R4W
SW | DLC
46
2008
PLS 1941

From which reference monuments:

- A 5/8"x30" iron rod, 27" in the ground, w/PC bears N.23°33'31"W., 110.36 ft set post with BT tag attached
- A 5/8" iron rod, projecting 20" above ground, with 1 1/2" alum cap mkd. "F-14", bears N.89°26'09"W., 67.17 ft.