

PRIMARY CORNER DESCRIPTION NW Cor. Ledgerwood DLC #52

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Aaron Bowser, April 5, 1856 Approved, 1858

Set post from which
 A B.Oak 15" dia. bears S.30°E., 120 lks. dist.
 Raised mound with trench as per instructions.

Bureau of Land Management Dependent Resurvey by Lynn Roseberry
under Group No. 636, Survey May/June 1967 (DCSO records,
Volume 34 Page 14204)

Corner perpetuated with an iron pipe, 2 ft. long ½" dia.
protruding 1" above ground, firmly set in the corner of the
wire fences extending E. and S. This corner was shown to me
by J. Ingram, an interested property owner, and is accepted as
the best available evidence of the original corner.

At the corner point, Set an iron post, 28" long, 2½" dia., 24"
in the ground, with brass cap mkd.

 T 27 S R 4 W
 S 32 |
 C 52
 1967

from which
 A Fir 25" dia. bears S.61¾°E., 163½ lks. dist., mkd.
 C 52 BT.
 A Fir 68" dia. bears S.8¼°E., 84 lks. dist., mkd.
 C 52 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/10/2000 - C.S. File 66/14-21

Looked for not found.

Mark Smalley - For: Roseburg Resources - 5/9/2006 - C.S.
65/60-2

Found - 1967 BLM IPBC
New - 8" Madrone, S.46°E., 5.7 scribed "DLC BT"
 7" Madrone, S.76°E., 47.3 scribed "DLC BT"