

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & 25 of T27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, Contract #1 dated May, 1851
(DCSO records, Volume 12 Page 5040 and 5042)

Set ¼ sec. post, from which
 A B.Oak 12" dia. bears S.10°E., 50 lks. dist.
 A B.Oak, 12" dia. bears S.20°W., 125. lks. dist.

James W. Byron, Deputy - Milo Godfrey; S.A. Bilow
Jan. 23, 1959 - C.S. 49/130-14

Found - Orig. 12" now 24" B.Oak S.20°W., 82.5 ft., I
 open & find good scribing "S".
 No trace of original SE BT found.
Set - Brass cap at cor. mkd. County Surveyor's Office
 ¼ S 25 | S 30
 R5W R4W
 1959

New BTs - 14" R.Fir bears N.21°E., 19.5 ft. scribed ¼ S30 CSBT
 11" R.Fir bears S.72°W., 24.7 ft. scribed ¼ S25 CSBT
Note - N-S fence 4 ft. west.

Doug. County Surveyors Office - Randall Smith; Stephen Flause
April 27, 1993 - C.S. File 64/43-20

Found - 2½" dia. 1959 DCSO brass cap on 1½" O.D. I.P. pro-
 truding 12" above ground
 12" now 26" dia. 3 ft high B.Oak stump, possible
 healed lower blaze, fallen Oak tree along West
 side, re-opened previously opened blaze, find
 blaze, axe marks and illegible scribing.
 Stump bears S.20°W., 79.8 ft. (Rec. S.20°W.,
 82.5 ft.) Area of cor. is on a steep North
 slope, which may account for dist. problem.
 (Orig. BT.)
 11" now 22" dia. D.Fir with a fully healed double
 blaze bears S.72°W., 24.0 ft. (Rec. S.72°W.,
 24.7 ft. 1959 BT.)
 14" now 18" dia. 1½ ft. high D.Fir stump, I opened
 a lower blaze and find scribe marks "BT", stump
 bears N.21°E., 18.7 ft. (Rec. N.21°E., 19.5
 ft.) 1959 BT.
New BTs - 18" D.Fir double blazed and scribed "¼ S25 CS BT"
 bears N.47½°W., 34.3 ft

(Cont. Next Page)

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; S. 25 of T. 27-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

17" Madrone, bark scribed "¼ S30 CS BT" bears
S.64½°E., 19.7 ft.
9" D.Fir double blazed and scribed "¼ S30 CS BT"
bears N.59°E., 30.1 ft.
Corner lies 4 ft. East of a North-South fence line on a steep
North slope.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
3/17/2008 - C.S. File 67/25-34

Fd. BC & 3 live BTs & 2 BT stumps