

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. 7 & 18; 12 & 13, T.27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, Contract #1 dated May 28, 1851. (DCSO Records, Volume 5039 and 5042)

Set post, cor. of secs. 7, 12, 13, & 18, from which
A B.Oak, 10" dia. bears N.26°E., 50 lks. dist.
A B.Oak, 12" dia. bears S.75°E., 47 lks. dist.
A B.Oak, 18" dia. bears S.75°W., 45 lks. dist.
A B.Oak, 18" dia. bears N.85°W., 90 lks. dist.

Ben. B. Irving, County Surveyor for: California Oregon
Power Co. - April, 1953 - C.S. 45/150

Set - 1" Pipe & brass cap mkd. County Surveyors Office
Corner Sec. 12 & 13, R 5 W
Corner Sec 7 & 18, R 4 W

From which:
A B.Oak, 30" bears N.26°E., 33.0 ft. (OBT) Rescribed
A B.Oak, 36" bears S.75°E., 30.8 ft. (OBT) Rescribed
A B.Oak, 36" bears N.85°W., 60.8 ft. (OBT) Rescribed
A B.Oak, (snag) 36" bears S.75°W., 29.7 ft.
New BT - 36" B. Oak S.60°W., 81.8 ft. blazed & scribed.

Fd. OK - Raleigh, RM 3 - 70 A&B - Dec. 1988
Fd. B.C. Aug. 1990 - 1990-0055

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/27/94 - C.S. File 64/50-4

Found - 2½" dia., brass cap on 1½" O.D. iron pipe protruding
6" above ground.
20" now 30" dia., dead B.Oak with a fully healed
single blaze bears N.22°E. 33.8' (Rec. N.26°E.,
33.0' dist. possible face measurement) OBT
12" now 33" dia., B.Oak with a partially healed
open blaze no scribing visible, bears S.77½°E.,
29.0' (Rec. S.75°E., 30.8') OBT
18" now 35" dia., 12' high alive B.Oak with sawed
off top and a fully healed single blaze bears
N.82½°W., 57.3' (Rec. N. 85°W., 60.8' dist. is
a slope measurement) OBT

Orig. SW BT now gone.

(Cont. Next Page)

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. 7 & 18; 12 & 13, T.27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

36" dia., now 36" dia., 2' high B.Oak stump, no blazes or scribing visible, bears S.62½°W., 81.8' (Rec. S.60°W., 81.8') 1953 BBI
New BTs - 15" dia., W.Oak double blazed and scribed "T27S R5W S12 CS BT" bears N.39½°W., 21.4'.
12" dia., W.Oak double blazed and scribed "T27S R4W S7 CS BT", bears N.31¼°E., 105.1'.
See sketch in file.

Fd. OK - Maurice Farr - Dec. 1995 - M 123-16
Found OK by K. DeGroot, Dec. 2002 - 2003-0038