

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7; & S. 12, T27-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, Contract #1 dated May, 1851  
(DCSO records, Volume 12 Page 5039 & 5042)

-----  
Set ¼ sec. post, from which  
    A Willow, 11" dia. bears S.22°E., 137 lks. dist.  
    A Willow, 12" dia. bears S.26°E., 125 lks. dist.

-----  
Glenn S. Baughman - For: Snowbird Stone - Aug. 1970  
Filed Jan. 19, 1971 - M 41 - 7

-----  
Set ¼ cor. by proportional measurement.  
Set - Brass cap stamped.  
Scribed - 36" Alder bears S.33°W., 243.2 ft.  
          11" W.Oak bears N.68°E., 350.5 ft.

-----  
Glenn Baughman - For: Kenneth Miller - Jan. 1984 - M 95-73

-----  
Found - 1¼" I.P. with brass cap attached.  
          24" double Ash (Rec. Alder) S.36°41'W., 243.2 ft.  
                    scribe visible. (Rec. S.33°W., 243.2 ft.)  
          12" W.Oak stump N.67°05'E., 352.1 ft. (Rec. N.68°E.  
                    350.5 ft.)  
Set - R.P. spike in PP & L Pole No. "6/99 R", S.34°05'E.,  
          142.1 ft.

-----  
Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/24/94 - C.S. File 64/50-16

-----  
Found - 2½" dia. brass cap on 1¼" O.D. iron pipe protruding  
          3" above ground. (1970)  
          24" now 41" dia., double trunked Ash with a  
          partially healed double blaze on 24" dia.,  
          Northerly trunk "¼ S12 BT" root crown bears  
          S.35¼°W. 243.2' (Rec. S.36°41'W. 243.2') 1970.  
          NE Oak now gone (1970)  
          R.P. spike in PP&L pole No. 6/99 R is gone (1984)  
          replacement pole marked "91 DFPA 60 HI 85"  
          bears S.35½°E., 143.1'.

(Cont. Next Page)

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7; & S. 12, T27-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -

5'x13'x2' high concrete water trough, SE corner bears N.12°E., 88.4'.

5/8" I.R. with alum. cap mkd: "PAC PWR LGT CO LS 888" protrudes 2" above ground in Easterly R/W fence of Diamond Lake Hwy we add the marks "B01", bears S.71½°W., 280.82'.

5/8" I.R. with alum. cap mkd: "PAC PWR LGT CO LS 888" protrudes 2" above ground in Easterly R/W fence of Diamond Lake Hwy we add the marks "B02" bears N.89¼°W., 229.83'.

See sketch in file.

Note - Corner lies 54' South of a random fence line in swampy area.

Fd. Ok by K.DeGroot, 7/2005 - M146-23

Douglas Co. Surveyors Office - John Pike - Kody Inda-  
3/24/2008 - C.S. File 67/25-36

-----  
Fd. Ok as per DCS0 1994 Rec.

Fd. BC/IP 10/2022 - M Heimburger - M181-59