TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor Sec 6 & Sec. 1, T.27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, contract #1 dated May 1851
(DCSO records, Volume 12 Page 5039 & 5042)

Set ¼ sec. post, from which
A W.Oak, 20" dia. bears S.53°E., 140 lks. dist.
A W.Oak, 7" dia. bears N.2°30'W., 140 lks. dist.

Milo Godfrey, Deputy - Wm. Stoffel; Mike Stone
January, 1964 - C.S. 53/33-4

Found - 42" W.Oak, S.53°E., 92.4 ft. cut open & fd. good scribing "BT".
Stump hole & small pieces of Oak, N.2½°W., 92.4 ft.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
T27S R5W ¼ S|S6 R4W
New BTs - 8" W.Oak N.81°W., 22.5 ft. mkd. ¼ S1 CS BT.
9" W.Oak S.75°E., 28.6 ft. mkd. ¼ S6 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/7/94 - C.S. File 64/50-5

Found - 2½" dia., brass cap on a 1¼" O.D. iron pipe protruding 9" above ground. 1967
20" now 26" dia. 3' high burnt oak stump with scribe marks visible "BT" bears S.55°E., 92.4' (Rec. S.53°E., 92.4') OBT
8" now 9" dia., W.Oak with a fully healed double blaze, bears N.81°W. 22.5' (Agrees w/rec.) 1964
9" now 14" dia., w.Oak with a fully healed double blaze, bears S.75°E., 28.6' (Agrees w/rec) 1964
Orig. NW BT now gone.
New BTs - 19" dia., W.Oak double blazed and scribed "¼ S6 CS BT", bears N.66½°E., 56.6'.
17" dia., W.Oak double blazed and scribed "¼ S1 CS BT", bears S.44½°W., 23.7'.
See sketch in file.