

PRIMARY CORNER DESCRIPTION W 1/16 N. line Sec. 6, T28-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

C.C. Boyer, Deputy Co. Surveyor, June, 1913 For: L. Hatfield
Volume 2 Page 178 - F.B. 35 Pages 3-11

Set post 4x4x36 mkd: CS 1/16 S, from which:
 A R.Fir, 10" dia., bears S.57°W., 45 lks., mkd: CS 1/16 S
 BT.
 A R.Fir, 26" dia., bears S.17°E., 85 lks., mkd: CS 1/16 S
 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/5/2000 - C.S. File 66/14-2

Perpetuated corner set in 1913
Found - 3/4" I.D. iron pipe protrudes 11" above ground
 possibly set in 1927 C.S. 1/64 (Note: map in file
 shows a double circle but doesn't say if corner
 is found or set. DCSO jc 1/25/2000)
 10" now 21" 3 ft. high rotted D.Fir stump, scribing
 Fd. "CS" bears S.57°W., 29.7 ft. 1913
 26" now 26" 2½ ft. high rotted D.Fir stump, bark
 scribing visible "1/1", bears S.17°E., 54.8 ft.
 (Rec. S.17°E., 56.1 ft.) 1913
New BTs- 19" dia., W.Fir single blazed low & scribed "X CS
 BT" bears N.72°E., 36.9 ft.
 16" dia., D.Fir single blazed low & scribed "X CS
 BT" bears S.57°W., 33.9 ft.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 3/17/2008 - C.S. File 67/25-34

Fd. ¾" ID iron pipe, 2 live BTs & 2 BT stumps as per DCSO
2000 rec.