

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5071)

Set 1/4 sec. post, from which
 A Laurel 6" dia. bears S.15°W., 48 lks. dist.
 A W.Oak 18" dia. bears N.28°W., 55 lks. dist.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow
Feb. 17, 1959 - C.S. File 49/130-17

Found - Orig. 18" now 22" W.Oak N.28°W., 36.3 ft. I open &
 find good scribing "1/4 S".
 No trace of orig. SW BT.

Set brass cap at corner mkd: County Surveyors Office, 1959
 1/4 S 30 T27S R4W
 S 31

New BTs - 16" R.Fir bears N.2°W., 6.7 ft. scribed 1/4 S30 CS BT.
 14" W.Oak bears S.48°W., 63.0 ft. scribed 1/4 S31 CSBT

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 10/18/1999 - C.S. File 66/12-31

Found - 2 1/2" brass cap on a 1 1/2" O.D. iron pipe protrudes 11"
 above ground. 1959
 All BTs now gone, burnt out root holes found near
 rec. Bee 1959 DCSO ren.

New B0s- 5/8"x30" long iron rod with DCSO alum. cap stamped
 "B01" bears North 50.0 ft.
 5/8"x30" long iron rod with DCSO alum. cap stamped
 "B03" bears West 30.0 ft.
 11" dia., W.Oak double blazed & scribed "1/4 S30 CS
 BT" bears N.20°W., 221.0 ft.
 5/8"x30" long iron rod with DCSO alum. cap stamped
 "B02" bears South 20.0 ft.

Fd. Ok by Douglas Co. Surveyors Office - Stephen J. Flause -
John Pike - 4/26/2007 - C.S. File 67/21-32