

PRIMARY CORNER DESCRIPTION Sec Cor for Secs 31 & 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5046)

Set post cor. to secs. 31 and 32, from which
A Fir 3" dia. bears N.32°W., 16 lks. dist.
A Fir 3" dia. bears S.11°W., 22 lks. dist.
A Dogwood, 4" dia. bears N.43°E., 26 lks. dist.
A Cedar 4" dia. bears S.28°E., 17 lks. dist.

GLO Survey by W.H. Byars, Under contract #376 dated
January 22, 1881 (DCSO Records, Volume 12 Page 5079)

Section corner to secs. 5, 6, 31 and 32 cor. & bearing trees
all standing, viz:
A Fir 3" dia. bears N.32°W., 16 lks. dist.
A Fir 3" dia. bears S.11°W., 22 lks. dist.
A Dogwood 4" dia. bears N.43°E., 26 lks. dist.
A Cedar 4" dia. bears S.28°E., 17 lks. dist.

F.C. Frear, Deputy - Wit. S.J. Jones; C.J. Ingram; Henry
Weber - Nov. 18, 1921 - Map # M8-43 (Road Record 17 Pages
64-67)

I reestablished from one old BT. viz. 18" Cedar bears
S.28°E., 11.2 ft. marks plain & other trees all destroyed.
I set a 2" x 12" wagon boxing from which
A 24" Cedar bears S.82°W., 28.3 ft.

Milo Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone
Oct/Nov 1963 - C.S. File 53/33-29

Found - Iron wagon boxing set by Frear in 1921.
27" I.Cedar S.28°E., 11.2 ft. shows plain axe scar.
Tree alive & in good condition.
24" Cedar S.82°W., 28.3 ft., is uprooted & dead,
shows very plain axe scar. This tree marked by
Frear.
New BTs - 10" I.Cedar N.76°E., 57.5 ft. mkd: T27S R4W S32 CSBT
10" I.Cedar N.38°W., 85.6 ft. mkd: T27S R4W S31 CSBT
(Scribed high to get over fence wires)

PRIMARY CORNER DESCRIPTION Sec Cor for 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Dependent Resurvey, So. Bdy. Tsp.
Lynn M. Roseberry, Group #636. Survey, May/June 1967
(DCSO records, Volume 34 Pages 14193-4)

The standard cor. of secs. 31 and 32 only, perpetuated & re-
corded by F.C. Frear in 1921, monumented with an iron wagon
boxing, 2 x 12", protruding 1" above ground, firmly set, at
record bearing & distance from the remaining original BT:

A Cedar 27" dia. bears S.28°E., 17 lks. dist. with a
healed blaze.

and a bearing tree mkd. by Frear in 1921:

An uprooted Cedar 26" dia. bears S.82°W., 43 lks. dist.
with a healed blaze.

and bearing trees mkd. by Godfrey in 1963:

A Cedar 10" dia. bears N.75½°E., 87 lks. dist. with
scribe marks T27S R4W S32 CS BT visible on partially
healed blaze.

A Cedar 11" dia. bears N.38¼°W., 129½ lks. dist. with
scribe marks T27S R4W S31 CS BT visible on partially
healed blaze.

At the corner point, set a fiberglass post, 28" long 2½" dia.,
20" in the ground, with brass cap mkd:

S C
T 27 S R 4 W
S 31 | S 32
S 6
T 28 S R 4 W
1967

Reset the wagon boxing alongside the fiberglass post.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
3/13/2008 - C.S. File 67/25-32

Fd. BLM BC, 1 live BT, 2 BTs stumps, good cond. & BC at
closing cor. secs. 5 & 6 only (T28-4)