

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5070)

Set post cor. to secs. 29, 30, 31 and 32, from which
A B.Oak 20" dia. bears S.35°E., 404 lks. dist.
A B.Oak 16" dia. bears N.33°E., 152 lks. dist.
A Maple 8" dia. bears S.48°W., 485 lks. dist.
A W.Oak 7" dia. bears N.8°W., 306 lks. dist.

James W. Byron, Deputy - M. Godfrey; S.A. Bilow - January 23,
1959 - C.S. file 49/130-13

Found - Orig. 7" now 16" W.Oak N.8°W., 202.0 ft., I open &
find good scribing "S30".

No trace of other orig. BTs.

Set brass cap at cor. mkd: County Surveyor's Office, 1959

S30	S29
S31	S32

T27S R4W

Corner is in old E-W fence line.

New BTs - 10" B.Oak bears North 28.3 ft. scribed S30 T27S R4W
CS BT.

26" R.Fir bears S.73°W., 38.8 ft. scribed S31 T27S
R4W CS BT.

8" W.Oak bears N.83½°E., 48.7 ft. scribed S29 T27S
R4W CS BT.

10 W.Oak bears S.12°E., 18.6 ft. scribed S32 T27S
R4W CS BT.

Found DCSO brass cap, 1 orig. BT, and 4 renewal BTs.
BLM dependent resurvey, April, 1970 - (DCSO records, Volume
35 pages 14464-65)

Found OK, Donald Bentz, August 1987, M 101-26

Doug. County Surveyors Office - L.E. Monrean, Deputy - John
Pike - July 8, 1992 - C.S. File 64/26-18

Found - Iron pipe with brass cap, firmly set, 1 ft. high,
wood fence post along east edge. (1959 BC)

No original BTs found.

12" Oak N.82¼°E., not found. (1959)

30" Fir now dead, standing, 36" dia., with well
healed double blaze bears S.73°W., 38.3 ft.
(Rec. 38.9 ft. This tree to be removed.)

Continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" W.Oak now 18" dia. with well healed double blaze bears S.10½°E., 17.7 ft. (Rec. S.11½°E., 18.5 ft.)
13" B.Oak now 18" with well healed double blaze bears N.1½°W., 28.0 ft. (Rec. 29.0 ft.)
New BTs-21" dia. B.Oak double blazed & scribed "T27S R4W S30 CS BT" bears N.61°W., 103.4 ft.
26" dia. B.Oak double blazed & scribed "T27S R4W S32 CS BT" bears S.61°E., 195.1 ft.

Fd. Ok by Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 4/26/2007 - C.S. File 67/21-32