

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec Cor for 5 & 6; 31 & 32 of T26-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4427)

Set post cor. to secs. 31, 32, 6 & 5, from which
A B.Oak 8" dia. bears S.78°W., 69 lks. dist.
A Willow, 8" dia. bears N.42°W., 107 lks. dist.
A W.Oak 9" dia. bears N.70°E., 330 lks. dist.
A B.Oak 5" dia. bears S.53°E., 214 lks. dist.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone
January 1964 - C.S. File 53/33-61

Found - 21" W.Oak N.70°E., 217.8 ft. opened & found reverse
scribing "BT" on badly rotted pieces of over-
growth of old face.

No trace of any other BTs.

Set brass cap at cor. mkd: County Surveyors T26S R4W S31|S32
Office, 1964 T27S S 6|S 5

New BTs - 6" D.Fir S.67°E., 15.3 ft. mkd: T27S R4W S5 CS BT.
12" I.Cedar S.17°E., 88.8 ft. mkd: T27S R4W S5 CSBT.

No suitable trees available in any other quadrant.
Corner lies in E. edge of power line road, directly under
power wires. Gate post E. end steel gate in E & W fence line,
(scribed "B.O.") bears N.22°E., 16.0 ft.

Found OK, August 1987, Donald Bentz - M 101-26

Douglas Co. Surveyors Office - John Pike - Kody Inda -
3/25/2008 - C.S. File 67/25-3

Fd. ok, all accessories fd as noted in DCSO 1964 ren.
Note: D.Fir under power lines now topped.