

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 300120

PRIMARY CORNER DESCRIPTION S 1/16 Cor. Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bureau of Land Management Dependent Resurvey - James E. Jelley under Group No. 700, Survey April, 1970 (DCSO Records, Volume 35 Pages 14463-64)

Point for the 1/16 sec. cor. of secs. 32 & 33
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap marked: S 1/16
 S 32|S 33
 1970

from which BTs & a reference monument
 A Fir, 20" dia., bears S.64½°E., 117 lks., mkd: S 1/16 S
 33 BT.
 An iron post, 28" long, 2½" dia., 24" in the ground, for
 a reference monument, bears S.10½°E., 15 lks. with
 brass cap marked: S 1/16 S33 RM 1970, and an arrow
 pointing to the corner.
 A Fir, 18" dia., bears N.76½°W., 116 lks., mkd: S 1/16 S32
 BT.
Corner falls in a ravine, drains W.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith,
Deputy - Stephen J. Flause - 2/10/2000 - C.S. File 66/14-21