

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5064)

Set $\frac{1}{4}$ sec. post, from which
 A Laurel 14" dia. bears S.65°E., 20 lks. dist.
 A Laurel 8" dia. bears N.47°W., 39 lks. dist.

Bureau of Land Management Dependent Resurvey - James E. Jelley
under Group No. 700, Survey April, 1970 (DCSO Records, Volume
35 Pages 14463-64)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance, there is
no remaining evidence of the orig. corner.
Set an iron post, 28" long 2 $\frac{1}{2}$ " dia. 24" in the ground, with
brass cap mkd:

$\frac{1}{4}$
S32|S33
T 27 S R 4 W
1970

from which

A Fir 10" dia. bears S.67 $\frac{1}{2}$ °E., 11 $\frac{1}{2}$ lks. dist. mkd. $\frac{1}{4}$ S33 BT.
A Fir 12" dia. bears S.81 $\frac{1}{2}$ °W., 82 lks. dist. mkd. $\frac{1}{4}$ S32 BT.

Ken Hoffine - For: Pliket & Hatfield - April 2010 - C.S. File
65/69-17

(Corner report only)
Found - 1970 BLM brass cap
 20 D.Fir bears S67 $\frac{1}{2}$ °E., 7.6 ft as per record healed
 face and tag
 24 D.Fir bears S.81 $\frac{1}{2}$ °W., 54.12 ft as per record
 healed face and tag corner sits on north-east
 facing slope approx. 200 ft east and 150 ft
 north of ridge top.