

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5064-5)

Set post cor. to secs. 32, 33, 28 and 29, from which
A B.Oak 10" dia. bears N.75°E., 7 lks. dist.
A B.Oak 13" dia. bears S.86°E., 11 lks. dist.
A B.Oak 18" dia. bears S.29°W., 133 lks. dist.
A B.Oak 8" dia. bears N.85°W., 145 lks.

Bureau of Land Management Dependent Resurvey - James E.
Jelley under Group #700. Survey April, 1970 - (DCSO records,
Volume 35 page 14464)

Point for the cor. of secs. at proportionate distance; there
is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:

T 27 S R 4 W

S 29 | S 28

S 32 | S 33

1970

from which

A Fir 7" dia. bears N.20°E., 103 lks mkd. T27S R4W S28 BT
A Fir 7" dia bears S.20°E., 173 lks mkd T27S R4W S33 BT
A Fir 10" dia bears S.64¼°W., 128 lks mkd T27S R4W S32 BT
A Fir 12" dia bears N.71¾°W., 183 lks mkd T27S R4W S29 BT

Brass cap and 2 BTs found (SE & SW) by R.B. Kimberling
April, 1982; M 91-70

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/18/2000 - C.S. File 66/14-5

Found - 1970 BLM brass cap/iron pipe
1970 NE & SE BTs now gone.
No OBTs found.
10" now 22" dia., D.Fir with a fully healed single
blaze bears S.66½°W., 84.5 ft. (rec. S.64½°W.,
84.5 ft.) 1970

New BTs- 6" W.Oak double blazed & scribed "X CS BT" bears
S.63½°E., 90.7 ft.
10" dia., Madrone double blazed & scribed "T27S R4W
S33 CS BT" bears S.13°E., 109.5 ft.
North peak of large barn bears N.22°E.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
3/13/2008 - C.S. File 67/25-33

Fd. BC & 3 live BTs as per 2000 DCSO rec.