TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5065)

Set ¼ sec. post, from which
A R. Fir 10" dia. bears S.3°E., 29 lks. dist.
A Laurel, 2" dia. bears N.15°W., 50 lks. dist.

BLM Dependent Resurvey - James E. Jelley under Group #700. Survey April, 1970 (DCSO records, Volume 35 Page 14466)

Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia. 24" in the ground, with brass cap mkd: S 28
¼ S 33
T 27 S R 4 W
1970 from which
A Fir 14" dia. bears N.4°E., 51½ lks. dist. mkd. ¼ S28 BT
Deposit broken brown glass at base of iron post.
There is no suitable bearing tree available within limits in sec. 33.
Corner falls in old wire fence, bears E. and W.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/31/2000 - C.S. File 66/14-11

Found - 1970 BLM BC/IP protrudes 6" above ground in an old down E-W fence line.
14" 24" dia., D.Fir with a fully healed single blaze, bears N.4°E., 34.0 ft.
New BTs - 9" dia., Madrone bark scribed "¼ S33 CS BT" bears S.62½°E., 19.0 ft. to root crown.
12" dia., Madrone bark scribed "¼ S28 CS BT" bears N.27½°E., 5.0 ft.

Ken Hoffine - For: Lone Rock Timber Co - Feb. 2020 - M176-45

Found - 1970 BLM brass cap marked T27S R4W ¼ S28|S33
10" Pacific Madrone bears S.63°E., 17.8 ft. (record S.62½°E., 19.0 ft.) tag and healed face.
17" Pacific Madrone bears N.20¼°E., 5.2 ft. (record N.27½°E., 5.0 ft.) tag and partially visible scribe "¼".
32" D.Fir found at record N.4°E., 34.0 ft. healed face and tag.
Corner lies on West slope in open timber and grass approximately 100 ft east of dirt road in old down fence line 0.3 ft above ground level.